FIRE DOORSETS

from

TRADE TECH




ACCREDITATIONS



Certificates can be downloaded from warringtonfire.com

DOOR SET STYLES




DOOR SET COLOURS

INTERNAL & EXTERNAL COMBINATIONS AVAILABLE




FURNITURE COLOURS



GU Multipoint Lock

Stippolyte

DOOR SET WIDTHS



*Utility Cupboard Door is supplied without door closer and with "Fire Door Keep Locked" signage.

All measurements in millimetres

CLOSERS

The fire doorset is available with two options of surface mounted door closers. The TS72 closer can be fitted on the internal face of the door only, and the TS92 slide arm closer is suitable to be fitted to the internal or external face of the doorset. Both closers are available in gold and chrome finish and the fixing positions are pilot drilled for installation on site.



DORMA TS72

SURFACE MOUNTED

- ✓ Rack and pinion v-arm closer
- Surface mounted on internal face of doorset
- Variable closing force EN 2-4
- Tested and CE marked to EN 1154
- ✓ Third party certificated by Certifire under CF 268

Also available in Gold

DORMA TS92

SURFACE MOUNTED

- Cam action, slide arm closer
- Surface mounted on internal or external face of doorset
- Variable closing force EN 1-4
- Tested and CE marked to EN 1154
- Third party certificated by Certifire under CF 119

Also available in Chrome

SPECIFICATION OVERVIEW

SINGLE CERTIFICATION	FD30S Fire doorset tested to BS 476: Part 22 or BS EN 1634-1:2014 Certificated to BS 476:Part 22 by Warringtonfire Certifire scheme. Certificate number CF 5906. Tested for cold smoke leakage to BS EN 1634-3 Capable of meeting Approved Document Q (Part Q), Security – Dwellings.
DUAL CERTIFICATION	FD30S Fire and Security doorset tested to BS 476: Part 22 or BS EN 1634-1:2014 Certificated to BS 476:Part 22 and PAS 24:2016 by Warringtonfire Certifire and Certisecure schemes. Certificate numbers CS 5112 / CF 5863 Tested for cold smoke leakage to BS EN 1634-3 Accredited by Secured by Design
INTEGRITY/INSULATION	DSI fire doorsets are certificated for 30 minutes fire integrity and only suitable for use when fire insulation is required if the doorset has less than 20% of un-insulating glass, including any toplight.
FRAME	Timber hybrid frame. Low maintenance UPVC outer skin with sustainable sourced timber core rein- forcement providing structural stability for all key comportments.
TOPLIGHT CONSTRUCTION	Four sided frame with dedicated hardwood coupler
THRESHOLD OPTION	Low threshold in aluminum for accessibility
LOCKING MECHANISM	GU Multipoint slam lock with intumescent protection
CYLINDER	UAP Kinetica Euro Cylinder BSi 3* Kitemarked
GLAZED APERTURES	Insulated glass unit, argon filled with 7 mm Pilkington Pyrodur and 6.8 mm thick Pilkington K Clear laminated glass or Pilkington K P1A Stippolyte glass.
GLAZING CASSETTE	Colour matched cassette
HARDWARE / FURNITURE	Certifire approved TS008 letterplate with security cowl. Eyeviewer available at low and high height for wheelchair accessibility. Trojan Surface mounted knocker. Fully suited in gold /chrome. Trojan surface mounted urn knocker. Fully suited in gold or chrome
HANDLE TYPE	Lever/Lever Solid Spindle
HINGE TYPE	3 x Grade 13, CE marked stainless steel butt hinges in chrome with intumescent protection.
CLOSER	Certifire approved surface closers, Dorma TS72V arm closer and Dorma TS92 slide arm closer. Pilot holes prepared for installation on site.

SINGLE CERTIFICATED





DUAL CERTIFICATED

603 Fire Deer Certification unless installed and mail exactly in accordance LTD Manufacturer's instruction is this tabel is r unmarked and not re

invalid with spe and proved, bookst b



6Wf

CERTOFIRE

Verringtonfiles CESTI12 / CF5863 / 20 / 000001 Door-Stop International Secure Door-Stop International Fire and Security Door TEL: 01623 446 336

Dual scope fire and security certification invalid unless installed and maintained exactly in accordance with the mainulacture's instructions and this label is retained unmarked and not removed.

